

ARRS1

Part Number 941201000002



- Includes:
- (1) 120 V.A.C. Rope Rescue Device
 - (1) Foot Switch
 - (1) Hitch Extension
 - (1) Carrying Case



SPECIFICATIONS

Storage Dimensions in Carrying Case

Length:	24.0 in.	(609.6 mm)
Width:	19.5 in.	(495.3 mm)
Height:	14.0 in.	(355.6 mm)
Weight (Hoist Assembly)	66.0 lbs.	(25.0 kg)
Total Weight	100 lbs.	(45.4 kg)
(Including foot switch & hitch extension, carrying case)		
Working Capacity:	1,000 lbs	(454.0 kg)
Power supply requirement:	115 V.A.C. /20 Amps	
Full load draw:	14 Amps	

Receiver hitch requirement:	Minimum Class IV rated with a minimum capacity of 10,000 lbs. (4536.0 kg)
Rope Requirement:	1/2" to 5/8" Rescue Rope (12.5mm to 16mm)
Maximum Rope Speed:	40 feet per minute up to full load

DESIGN & OPERATIONAL FEATURES

- ★ Sets up in under two minutes.
- ★ Reduces number of rescuers needed topside (2 people can do the work of approximately 8-10 used in traditional rope rescue).
- ★ Passes knots with ease.
- ★ Rope automatically aligns with the direction of the load.
- ★ Precise control allows a load to be raised and lowered a fraction of an inch at a time for critical precision lifting.



AMKUS
RESCUE SYSTEMS

4201 Montdale Drive
Valparaiso, IN 46383-4098
219-548-5000
800-592-6587
Fax: 219-476-1669