

iS240 Spreader



SPECIFICATIONS

Length	30.1 in.	(746 mm)
Width	7.0 in.	(177 mm)
Height	8.8 in.	(223 mm)
Weight (excl. battery)	46.2 lbs.	(21.0 kg)
Max Spreading Distance	24.0 in	(609 mm)
Max Spreading Distance (with optional ERT tips)	32.0 in	(813 mm)
Battery	DeWalt® Lithium-ion	
Battery Voltage	36V	

DESIGN & OPERATIONAL FEATURES

- Lightweight aluminum enclosure is not susceptible to cracking like plastic housings
- Short length of tool allows it to fit into confined spaces competitive tools can't access
- Audible change in operation indicates when the battery is low
- Tool will not suddenly stop operating due to a low battery without warning
- Battery removal is to the side of the tool making it less susceptible
- Spreader uses the same tips as the AMK-24 & AMK-30CRT, including the ERT tips and quick adjust chain package.
- Ergonomic handle and control valve makes tool easy to operate in all positions
- Each tool is provided with two DeWalt® 36V lithium-ion batteries and one heavy duty charger
- DeWalt® batteries are compatible/interchangeable with all 36V DeWalt® equipment



4201 Montdale Drive
Valparaiso, IN 46383-4098
219-548-5000
800-592-6587
Fax: 219-476-1669